

IN THE CLAIMS

Kindly cancel claims 8 and 9, and amend claims 1, 4, and 5, as shown in the following claim listing:

1. (currently amended) An optical coherence tomography system comprising
 - an optical source to emit an optical beam
 - a sample space
 - a photodetector
 - an interferometer set-up including
 - a reference reflector and
 - a beam splitter-combination arrangement to
 - split the optical beam into a reference beam to the reference reflector and a sample beam to the sample space and to
 - combine a reflected beam from the reference reflector with a returning beam from the sample space on the photodetector, wherein
 - the optical source has an emission wavelength in the range of 1.6 μ m to 2.0 μ m, ~~in particular having an infrared emission predominantly at a wavelength of 1.8 μ m~~ associated with a transition between an upper energy level and a lower energy level and

- the optical source comprises an excitation system which generates stimulated emission from a pump level to the upper energy level.

2. (original) An optical coherence tomography system as claimed in Claim 1, wherein the optical source includes a Tm-doped fibre placed in an optical cavity of cavity reflectors facing one another.

3. (original) An optical coherence tomography system as claimed in Claim 2, wherein the cavity reflectors are anti-reflex coated for a wavelength range of 760nm to 810nm.

4. (currently amended) An optical coherence tomography system as claimed in Claim 2, wherein the cavity reflectors have a high-reflectivity ~~(coating)~~ for the wavelength range 2.2 μ m to 2.4 μ m.

5. (currently amended) An optical coherence tomography system as claimed in Claim 2, wherein the cavity reflectors have a high-reflectivity ~~(coating)~~ for the wavelength range 2.2 μ m to 2.4 μ m and/or for the wavelength range 1.40 μ m to 1.5 μ m.

6. (original) An optical coherence tomography system as claimed in Claim 2, wherein the optical cavity has reflectivities less than 0.04 for the wavelength range of 1.6-2.0 μ m.

7. (original) An optical coherence tomography system as claimed in Claim 6, wherein

- an input cavity reflector has a high reflectivity (coating) for the wavelength range 1.6 μ m to 2.0 μ m and
- an output cavity reflector has a low-reflectivity (coating) for the wavelength range 1.6 μ m to 2.0 μ m.

8. (cancelled)

9. (cancelled)